Universidad Politécnica de Cartagena. ETSII. Dpto. de Tecnología Electrónica
Diseño y Simulación Electrónica (507102009). 04/07/2014 (**1º PARCIAL**)

Calificación:	

Apellidos ..... Nombre .....DNI.....

1.- Diseñe y calcule una fuente de alimentación regulada lineal con los siguientes datos: (**3.33 puntos**).

Datos:
Tensión de entrada: $220V_{ef}$ *50Hz*
Tensión de salida: *14V, 0.8A,* $\Delta V_{PPCarga} = 10mV_{PP}$
Los datos adicionales que pueda necesitar los tiene en la tabla adjunta.

Realice: Dibuje el circuito completo del diseño elegido. Calcule los valores de todos los componentes que le sean necesarios para el correcto funcionamiento del mismo. Explique, justificadamente, las decisiones que vaya tomando. Obtenga, a su criterio, los datos que necesite para completar el ejercicio de la tabla adjunta.

Absolute Maximum Ratings

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Input Voltage (V_O = 5V, 12V and 15V)	35V
Internal Power Dissipation (Note 1)	Internally Limited
Operating Temperature Range (T_A)	0°C to +70°C
Maximum Junction Temperature	
(K Package)	150°C
(T Package)	150°C
Storage Temperature Range	−65°C to +150°C
Lead Temperature (Soldering, 10 sec.)	
TO-3 Package K	300°C
TO-220 Package T	230°C

Electrical Characteristics LM78XXC (Note 2) 0°C ≤ Tj ≤ 125°C unless otherwise noted.

Output Voltage				5V			12V			15V			Units
Input Voltage (unless otherwise noted)				10V			19V			23V			
Symbol	Parameter	Conditions		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
V_O	Output Voltage	Tj = 25°C, 5 mA ≤ I_O ≤ 1A		4.8	5	5.2	11.5	12	12.5	14.4	15	15.6	V
		P_D ≤ 15W, 5 mA ≤ I_O ≤ 1A		4.75		5.25	11.4		12.6	14.25		15.75	V
		V_{MIN} ≤ V_{IN} ≤ V_{MAX}		(7.5 ≤ V_{IN} ≤ 20)			(14.5 ≤ V_{IN} ≤ 27)			(17.5 ≤ V_{IN} ≤ 30)			V
I_Q	Quiescent Current	I_O ≤ 1A	Tj = 25°C			8			8			8	mA
			0°C ≤ Tj ≤ +125°C			8.5			8.5			8.5	mA
$\frac{\Delta V_{IN}}{\Delta V_{OUT}}$	Ripple Rejection	f = 120 Hz	I_O ≤ 1A, Tj = 25°C or	62	80		55	72		54	70		dB
			I_O ≤ 500 mA	62			55			54			dB
			0°C ≤ Tj ≤ +125°C										
		V_{MIN} ≤ V_{IN} ≤ V_{MAX}		(8 ≤ V_{IN} ≤ 18)			(15 ≤ V_{IN} ≤ 25)			(18.5 ≤ V_{IN} ≤ 28.5)			V
R_O	Dropout Voltage	Tj = 25°C, I_{OUT} = 1A			2.0			2.0			2.0		V
	Output Resistance	f = 1 kHz			8			18			19		mΩ
	Short-Circuit Current	Tj = 25°C			2.1			1.5			1.2		A
	Peak Output Current	Tj = 25°C			2.4			2.4			2.4		A
	Average TC of V_{OUT}	0°C ≤ Tj ≤ +125°C, I_O = 5 mA			0.6			1.5			1.8		mV/°C

Note 1: Thermal resistance of the TO-3 package (K, KC) is typically 4°C/W junction to case and 35°C/W case to ambient. Thermal resistance of the TO-220 package (T) is typically 4°C/W junction to case and 50°C/W case to ambient.

Note 2: All characteristics are measured with capacitor across the input of 0.22 μF, and a capacitor across the output of 0.1μF. All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques (t_w ≤ 10 ms, duty cycle ≤ 5%). Output voltage changes due to changes in internal temperature must be taken into account separately.